NSN 5910-01-407-6742

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-407-6742

view Online at https://acrobasegroup.com/nsn/5510-01-401-0142
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.001
Terminal Length:
1.250 inches
Body Length:
0.290 inches
Body Width:
0.290 inches
Body Height:
0.090 inches
Center To Center Distance Between Terminals Parallel To Length:
0.200 inches
Terminal Diameter:
0.026 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
120000.000 picofarads single section
Voltage Tempurature Limits Per Section In Percent Capacitance Change:
-15.0/+15.0 with rated voltage applied single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Terminal Surface Treatment:
Solder
Test Data Document:
81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-39014/02 government specification

Shelf Life:

N/a

NSN 5910-01-407-6742

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A010b0