

View Online at <https://aerobasegroup.com/nsn/5910-01-408-1088>

**Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.100

**Terminal Length:**

Between 2.250 inches and 2.750 inches

**Body Diameter:**

Between 0.735 inches and 0.765 inches

**Body Length:**

Between 2.125 inches and 2.328 inches

**Terminal Diameter:**

Between 0.038 inches and 0.048 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case, w/gnd terminal

**Impedance At Minimum Operating Temperature In Ohms:**

5.6

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

470.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 105.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

474.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Tolerance Range Per Section:**

-10.00/+30.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.28

**Dc Leakage At Reference Temp:**

79.000 microamperes

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Test Data Document:**

Mil-c-39018/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Specification Data:**

Mil-c-39018/3 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0

**Mil-std (military Standard):**

Mil-c-39018 spec.