

View Online at <https://aerobasegroup.com/nsn/5910-01-409-0642>

**Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.010

**Terminal Length:**

2.250 inches

**Body Diameter:**

Between 0.265 inches and 0.297 inches

**Body Length:**

Between 0.625 inches and 0.672 inches

**Terminal Diameter:**

0.025 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case, w/gnd terminal

**Electrical Polarization:**

Polarized

**End Application:**

Pacer dawn

**Features Provided:**

Hermetically sealed case

**Capacitance Value Per Section:**

220.000 microfarads single section

**Nonderated Operating Temp:**

Between 55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

30.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

42.000

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0