NSN 5910-01-411-6110

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-411-6110

| view Offilite at https://aerobasegroup.com/nsh/5510-01-411-0110 |
|---|
| Body Style: |
| W/o mtg facilities terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.137 inches and 0.177 inches |
| Body Length: |
| 0.177 inches |
| Body Width: |
| 0.288 inches |
| Body Height: |
| 0.100 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.200 inches |
| Terminal Diameter: |
| 0.020 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| End Application: |
| 6625-01-363-6212 multimeter |
| Capacitance Value Per Section: |
| 2200.000 picofarads single section |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |
| -10.0/+10.0 with rated voltage applied single section |
| Nonderated Operating Temp: |
| Between -30.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Plastic |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.150 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5910-01-411-6110

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0