NSN 5910-01-412-4340

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-412-4340

view Offilite at https://aerobasegroup.com/hist//3510-01-412-4540
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
1.250 inches
Body Length:
0.290 inches
Body Width:
0.290 inches
Body Height:
0.090 inches
Center To Center Distance Between Terminals Parallel To Length:
Between 0.185 inches and 0.215 inches
Terminal Diameter:
Between 0.023 inches and 0.029 inches
Capacitance Value Per Section:
12.000 nanofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
100000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
2.500
Test Data Document:
81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 uninsulated wire lead
Specification Data:

N/a

Shelf Life:

Unit Of Measure:

81349-mil-c-39014/2 government specification

--

NSN 5910-01-412-4340

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demi			

No

Fiig:

A010b0