## NSN 5910-01-413-0376

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-413-0376

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.001
Terminal Length:
1.000 inches
Body Length:
0.300 inches
Body Width:
0.330 inches
Body Height:
0.100 inches
Center To Center Distance Between Terminals Parallel To Length:
1.500 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
62.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
500.0 dc single section
Tolerance Range Per Section:
-2.00/+2.00 percent single section
Case Material:
Ceramic
Terminal Surface Treatment:
Solder
Test Data Document:
81349-mil-c-39001 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 uninsulated wire lead
Specification Data:
Mil-c-39001/5 government specification
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

## NSN 5910-01-413-0376

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0

Mil-std (military Standard):

Mil-c-39001 spec.