

View Online at <https://aerobasegroup.com/nsn/5910-01-413-5080>

Body Style:

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

5.0 millimeters

Body Length:

18.0 millimeters

Body Width:

15.0 millimeters

Body Height:

8.0 millimeters

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Kilauea class t-ae 26; forrestal class cv; wasp class lhd; oliver perry class ffg; los angeles class ssn (688); ticonderoga class cg (47); spruance class dd (963); mine countermeasures support (mcs) class (lph-12); arleigh burke class ddg; nimitz class cvn

Capacitance Value Per Section:

1.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 ac/dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Plastic

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0