

View Online at <https://aerobasegroup.com/nsn/5910-01-413-5091>

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Body Diameter:

1.023 inches

Body Length:

1.687 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Electrical Polarization:

Polarized

End Application:

Wasp class lhd; nimitz class cvn; kilauea class t-ae 26; mine countermeasures support (mcs) class (lhp-12); ticonderoga class cg (47); arleigh burke class ddg; los angeles class ssn (688); forrestal class cv; oliver perry class ffg; spruance class dd (963)

Capacitance Value Per Section:

4700.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00/+100.00 percent single section

Capacitive Electrode Material:

Aluminum

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0