NSN 5910-01-413-6958

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-413-6958

Body	Style:
------	--------

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

0.500 inches

Body Length:

Between 0.540 inches and 0.560 inches

Body Width:

0.400 inches

Body Height:

Between 0.230 inches and 0.250 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.390 inches and 0.410 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Insulation Resistance At Maximum Operating Temp:

500.0 megohm-microfarads

Capacitance Value Per Section:

0.150 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

25000.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

0.300

Terminal Surface Treatment:

Solder

Dielectric Material:

Plastic polycarbonate

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

NSN 5910-01-413-6958

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0