NSN 5910-01-413-7090

Glass Dielectric Variable Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-413-7090
Thread Class:
2a
Body Style:
Piston
Overall Length:
0.960 inches
Terminal Length:
1.500 inches
Body Length:
0.710 inches
Overall Diameter:
0.240 inches
Terminal Width:
0.025 inches
Mounting Facility Screw Thread Series Designator:
Unef
Bushing Shape:
Round
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 1 threaded bushing
1 threaded bushing
1 threaded bushing Thready Qty Per Inch (tpi):
1 threaded bushing Thready Qty Per Inch (tpi): 32
1 threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size:
1 threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.250 inches
1 threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.250 inches Capacitance Range In Picofarads:
1 threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.250 inches Capacitance Range In Picofarads: +0.6/+5.5 single section
1 threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.250 inches Capacitance Range In Picofarads: +0.6/+5.5 single section Nonderated Voltage Rating And Type:
1 threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.250 inches Capacitance Range In Picofarads: +0.6/+5.5 single section Nonderated Voltage Rating And Type: 1250.0 dc continuous single section
1 threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.250 inches Capacitance Range In Picofarads: +0.6/+5.5 single section Nonderated Voltage Rating And Type: 1250.0 dc continuous single section Terminal Type And Quantity:
1 threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.250 inches Capacitance Range In Picofarads: +0.6/+5.5 single section Nonderated Voltage Rating And Type: 1250.0 dc continuous single section Terminal Type And Quantity: 2 wire lead
1 threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.250 inches Capacitance Range In Picofarads: +0.6/+5.5 single section Nonderated Voltage Rating And Type: 1250.0 dc continuous single section Terminal Type And Quantity: 2 wire lead Shelf Life:
1 threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.250 inches Capacitance Range In Picofarads: +0.6/+5.5 single section Nonderated Voltage Rating And Type: 1250.0 dc continuous single section Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
1 threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.250 inches Capacitance Range In Picofarads: +0.6/+5.5 single section Nonderated Voltage Rating And Type: 1250.0 dc continuous single section Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
1 threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.250 inches Capacitance Range In Picofarads: +0.6/+5.5 single section Nonderated Voltage Rating And Type: 1250.0 dc continuous single section Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:
1 threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.250 inches Capacitance Range In Picofarads: +0.6/+5.5 single section Nonderated Voltage Rating And Type: 1250.0 dc continuous single section Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: