

View Online at <https://aerobasegroup.com/nsn/5910-01-416-0312>

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

Between 5.3 millimeters and 7.3 millimeters

Body Diameter:

22.0 millimeters

Body Length:

31.5 millimeters

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.9 millimeters and 1.1 millimeters

Terminal Diameter:

Between 0.7 millimeters and 1.0 millimeters

Schematic Diagram Designator:

No common or grounded electrode (s)

Electrical Polarization:

Polarized

End Application:

4920-01-339-9447 adapter, test

Capacitance Value Per Section:

100.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

250.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dc Leakage At Reference Temp:

0.470 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0