## NSN 5910-01-422-1699

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-422-1699 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 20.0 millimeters **Body Diameter:** 12.5 millimeters **Body Length:** 40.0 millimeters **Center To Center Distance Between Terminals Parallel To Diameter:** 5.0 millimeters **Terminal Diameter:** 0.6 millimeters **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 2200.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum Dc Leakage At Reference Temp: 0.030 microamperes **Reference Tempurature At Which Rated:** 20.0 degrees celsius **Terminal Surface Treatment:** Solder **Case Insulation Material: Plastic** 

Terminal Type And Ou

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-422-1699

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0