## NSN 5910-01-422-9231

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-422-9231

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.500 inches
Body Length:
0.420 inches
Body Width:
0.300 inches
Body Height:
0.180 inches
Center To Center Distance Between Terminals Parallel To Length:
0.400 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
Penguin launc
Insulation Resistance At Maximum Operating Temp:
100.0 megohms
Capacitance Value Per Section:
0.068 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Range Per Section:
-1.00/+1.00 percent single section
Case Material:
Plastic
Flastic
Insulation Resistance At Reference Temp:
Insulation Resistance At Reference Temp:
Insulation Resistance At Reference Temp: 50000.0 megohms
Insulation Resistance At Reference Temp: 50000.0 megohms Terminal Surface Treatment:
Insulation Resistance At Reference Temp: 50000.0 megohms Terminal Surface Treatment: Solder
Insulation Resistance At Reference Temp: 50000.0 megohms Terminal Surface Treatment: Solder Dielectric Material:
Insulation Resistance At Reference Temp: 50000.0 megohms Terminal Surface Treatment: Solder Dielectric Material: Plastic polycarbonate

N/a

## NSN 5910-01-422-9231

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0