

View Online at <https://aerobasegroup.com/nsn/5910-01-423-5246>

**Body Style:**

Chip type

**Reliability Indicator:**

Not established

**Terminal Length:**

Between 0.039 inches and 0.063 inches

**Body Length:**

Between 0.279 inches and 0.295 inches

**Body Width:**

Between 0.165 inches and 0.175 inches

**Body Height:**

0.170 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

22.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

77.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

35.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

6.000

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.70

**Dc Leakage At Reference Temp:**

7.700 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 bonding pad

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0