## NSN 5910-01-424-8457

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-424-8457

Body Style:
W/o mtg facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.500 inches
Body Length:
2.910 inches
Body Width:
1.910 inches
Body Height:
4.250 inches
Center To Center Distance Between Terminals Parallel To Length:
0.810 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
50kw frequency converter
Capacitance Value Per Section:
30.000 microfarads single section
Nonderated Operating Temp:
, , ,
Between -55.0 degrees celsius and 90.0 degrees celsius
Between -55.0 degrees celsius and 90.0 degrees celsius
Between -55.0 degrees celsius and 90.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:
Between -55.0 degrees celsius and 90.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  240.0 ac-rms single section
Between -55.0 degrees celsius and 90.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  240.0 ac-rms single section  Tolerance Range Per Section:
Between -55.0 degrees celsius and 90.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  240.0 ac-rms single section  Tolerance Range Per Section:  -3.00/+3.00 percent single section
Between -55.0 degrees celsius and 90.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  240.0 ac-rms single section  Tolerance Range Per Section:  -3.00/+3.00 percent single section  Case Material:
Between -55.0 degrees celsius and 90.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  240.0 ac-rms single section  Tolerance Range Per Section:  -3.00/+3.00 percent single section  Case Material:  Metal
Between -55.0 degrees celsius and 90.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 240.0 ac-rms single section  Tolerance Range Per Section: -3.00/+3.00 percent single section  Case Material:  Metal  Terminal Surface Treatment:
Between -55.0 degrees celsius and 90.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  240.0 ac-rms single section  Tolerance Range Per Section:  -3.00/+3.00 percent single section  Case Material:  Metal  Terminal Surface Treatment:  Solder
Between -55.0 degrees celsius and 90.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 240.0 ac-rms single section  Tolerance Range Per Section: -3.00/+3.00 percent single section  Case Material:  Metal  Terminal Surface Treatment: Solder  Dielectric Material:
Between -55.0 degrees celsius and 90.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 240.0 ac-rms single section  Tolerance Range Per Section: -3.00/+3.00 percent single section  Case Material:  Metal  Terminal Surface Treatment: Solder  Dielectric Material:  Plastic polypropylene
Between -55.0 degrees celsius and 90.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  240.0 ac-rms single section  Tolerance Range Per Section:  -3.00/+3.00 percent single section  Case Material:  Metal  Terminal Surface Treatment:  Solder  Dielectric Material:  Plastic polypropylene  Terminal Type And Quantity:
Between -55.0 degrees celsius and 90.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  240.0 ac-rms single section  Tolerance Range Per Section:  -3.00/+3.00 percent single section  Case Material:  Metal  Terminal Surface Treatment:  Solder  Dielectric Material:  Plastic polypropylene  Terminal Type And Quantity:  2 quick disconnect, male, three blade
Between -55.0 degrees celsius and 90.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  240.0 ac-rms single section  Tolerance Range Per Section:  -3.00/+3.00 percent single section  Case Material:  Metal  Terminal Surface Treatment:  Solder  Dielectric Material:  Plastic polypropylene  Terminal Type And Quantity:  2 quick disconnect, male, three blade  Shelf Life:
Between -55.0 degrees celsius and 90.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 240.0 ac-rms single section  Tolerance Range Per Section: -3.00/+3.00 percent single section  Case Material:  Metal  Terminal Surface Treatment:  Solder  Dielectric Material:  Plastic polypropylene  Terminal Type And Quantity: 2 quick disconnect, male, three blade  Shelf Life:  N/a
Between -55.0 degrees celsius and 90.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 240.0 ac-rms single section  Tolerance Range Per Section: -3.00/+3.00 percent single section  Case Material:  Metal  Terminal Surface Treatment:  Solder  Dielectric Material:  Plastic polypropylene  Terminal Type And Quantity: 2 quick disconnect, male, three blade  Shelf Life:  N/a
Between -55.0 degrees celsius and 90.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  240.0 ac-rms single section  Tolerance Range Per Section: -3.00/+3.00 percent single section  Case Material:  Metal  Terminal Surface Treatment: Solder  Dielectric Material: Plastic polypropylene  Terminal Type And Quantity: 2 quick disconnect, male, three blade  Shelf Life: N/a  Unit Of Measure:

A010b0