## NSN 5910-01-425-1374

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-425-1374 **Body Style:** Chip type **Reliability Indicator:** Not established **Terminal Length:** 0.020 inches **Body Length:** 0.138 inches **Body Width:** 0.104 inches **Body Height:** 0.051 inches **Terminal Diameter:** 0.010 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 0.470 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 5.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: Ceramic **Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: Equivalent Series Resistance At Reference Tempurature In Ohms:** 8.00 Dc Leakage At Reference Temp: 0.500 microamperes

**Terminal Surface Treatment:** Solder

## NSN 5910-01-425-1374

Electrolytic Fixed Capacitor - Page 2 of 2



Sr	10	ria	ΙF	ea	tıı	re	٠.
O.	JE	ыa		сa	ιu	ıc	ъ.

Tantalum wire nib identifies anode positive terminal.

## **Terminal Type And Quantity:**

1 bonding pad w/standoff cones and 1 bonding pad

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0