NSN 5910-01-430-4677

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-430-4677

Body Style:					
W/o mtg facilities, terminal (s) on one surface					
Reliability Indicator:					
Not established					
Terminal Length:					
0.079 inches					
Body Length:					
0.296 inches					
Body Width:					
0.296 inches					
Body Height:					
0.536 inches					
Center To Center Distance Between Terminals Parallel To Length:					
0.196 inches					
Terminal Diameter:					
0.020 inches					
Schematic Diagram Designator:					
No common or grounded electrode (s)					
Capacitance Value Per Section:					
0.680 microfarads single section					
Nonderated Operating Temp:					
Between -55.0 degrees celsius and 85.0 degrees celsius					
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:					
400.0 single section					
Nandarated Continuous Valtage Bating And Type Box Sections					
Nonderated Continuous Voltage Rating And Type Per Section:					
100.0 dc single section					
100.0 dc single section					
100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:					
100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section					
100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section Tolerance Range Per Section:					
100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section Tolerance Range Per Section: -20.00/+20.00 percent single section					
100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material:					
100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic					
100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment:					
100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder					
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material:					
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polyester					
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polyester Terminal Type And Quantity:					
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polyester Terminal Type And Quantity: 2 uninsulated wire lead					

--

NSN 5910-01-430-4677

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	tariz	

No

Fiig:

A010b0