## NSN 5910-01-430-9144

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-430-9144 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 0.100 **Terminal Length:** 1.250 inches **Body Length:** 0.190 inches **Body Width:** 0.190 inches **Body Height:** 0.090 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.200 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 100.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material: Plastic Test Data Document:** 81349-mil-c-39014/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead w/terminal lug Shelf Life: N/a **Unit Of Measure:** 

Fiig: A010b0

No

**Demilitarization:**