

View Online at https://aerobasegroup.com/nsn/5910-01-433-2454

| Body Style: | |
|--|-----|
| Dual inline | |
| Reliability Indicator: | |
| Not established | |
| Terminal Length: | |
| Between 0.060 inches and 0.080 inches | |
| Body Length: | |
| Between 0.224 inches and 0.275 inches | |
| Body Width: | |
| 0.300 inches | |
| Body Height: | |
| 0.650 inches | |
| Center To Center Distance Between Terminals Parallel To Length: | |
| 0.100 inches | |
| Center To Center Distance Between Terminals Parallel To Width: | |
| 0.250 inches | |
| Schematic Diagram Designator: | |
| No common or grounded electrode (s) | |
| Insulation Resistance At Maximum Operating Temp: | |
| 10000.0 megohms | |
| Capacitance Value Per Section: | |
| 3300.000 microfarads single section | |
| Voltage Tempurature Limits Per Section In Percent Capacitance Chan | ge: |
| -25.0/+15.0 with rated voltage applied single section | |
| Nonderated Operating Temp: | |
| Between -55.0 degrees celsius and 125.0 degrees celsius | |
| Nonderated Continuous Voltage Rating And Type Per Section: | |
| 50.0 dc single section | |
| Tolerance Range Per Section: | |
| -10.00/+10.00 percent single section | |
| Case Material: | |
| Ceramic | |
| Insulation Resistance At Reference Temp: | |
| 100000.0 megohms | |
| Dissipation Factor At Reference Tempurature In Percent: | |
| 2.500 | |
| Terminal Surface Treatment: | |
| Solder | |
| Terminal Type And Quantity: | |
| 6 uninsulated wire lead | |
| Shelf Life: | |
| N/a | |
| | |

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0