

View Online at https://aerobasegroup.com/nsn/5910-01-433-2684

| Body Style: |
|---|
| Dual inline |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.060 inches and 0.080 inches |
| Body Length: |
| Between 0.224 inches and 0.275 inches |
| Body Width: |
| 0.300 inches |
| Body Height: |
| 0.360 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.010 inches |
| Center To Center Distance Between Terminals Parallel To Width: |
| 0.250 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Insulation Resistance At Maximum Operating Temp: |
| 10000.0 megohms |
| Capacitance Value Per Section: |
| 820.000 microfarads single section |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |
| -40.0/+15.0 with rated voltage applied single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 200.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Ceramic |
| Insulation Resistance At Reference Temp: |
| 100000.0 megohms |
| Dissipation Factor At Reference Tempurature In Percent: |
| 2.500 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 6 uninsulated wire lead |
| Shelf Life: |
| N/a |
| |



Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0