

View Online at https://aerobasegroup.com/nsn/5910-01-434-5732

| Body Style: | |
|-----------------------|--|
| Chip type | |
| Reliability Indicator | т. Т |
| Not established | |
| Terminal Length: | |
| Between 0.010 inche | es and 0.040 inches |
| Body Length: | |
| Between 0.165 inche | es and 0.195 inches |
| Body Width: | |
| Between 0.065 inche | es and 0.095 inches |
| Body Height: | |
| Between 0.020 inche | es and 0.080 inches |
| Schematic Diagram | ı Designator: |
| No common or grou | nded electrode (s) |
| Capacitance Value | Per Section: |
| 100000.000 picofara | ds single section |
| Voltage Tempuratu | re Limits Per Section In Percent Capacitance Change: |
| -15.0/+15.0 with rate | ed voltage applied single section |
| Nonderated Operat | ing Temp: |
| Between -55.0 degre | ees celsius and 125.0 degrees celsius |
| Nonderated Contin | uous Voltage Rating And Type Per Section: |
| 25.0 dc single sectio | n |
| Tolerance Range P | er Section: |
| -10.00/+10.00 perce | nt single section |
| Case Material: | |
| Ceramic | |
| Terminal Surface T | reatment: |
| Solder | |
| Terminal Type And | Quantity: |
| 2 bonding pad | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| | |