

View Online at <https://aerobasegroup.com/nsn/5910-01-434-6047>

Body Style:

W/thd mtg hol (s)/stud(s), terminal(s) on one surface

Reliability Indicator:

Not established

Body Length:

2.050 inches

Body Width:

2.050 inches

Body Height:

0.450 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.500 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Solid

Electrical Polarization:

Polarized

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

3 threaded mounting holes

Section Quantity:

5

Capacitance Value Per Section:

4100.000 microfarads all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.190 inches

Dc Leakage At Maximum Operating Temp:

250.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

10.0 dc all sections

Tolerance Range Per Section:

-20.00/+20.00 percent all sections

Case Material:

Plastic

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

100.000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0