Plastic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-434-7003

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

1.000

#### **Terminal Length:**

1.750 inches

**Body Diameter:** 

0.613 inches

**Body Length:** 

1.688 inches

**Terminal Diameter:** 

0.032 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

0.180 microfarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Plastic

#### **Terminal Surface Treatment:**

Solder

#### Test Data Document:

81349-mil-c-55514 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### Terminal Type And Quantity:

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-c-55514/10 government specification

#### Shelf Life:

N/a

### Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A010b0