NSN 5910-01-434-7250

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-434-7250 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.100 **Terminal Length:** 1.750 inches **Body Diameter:** 0.516 inches **Body Length:** 1.250 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 0.082 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material: Plastic Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polypropylene **Test Data Document:** 81349-mil-c-55514 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead **Specification Data:** 81349-mil-c-55514/10 government specification Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5910-01-434-7250

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0