Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-434-7250

## Body Style:

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

Reliability Failure Rate Level In Percent:

0.100

#### **Terminal Length:**

1.750 inches

**Body Diameter:** 

0.516 inches

**Body Length:** 

1.250 inches

**Terminal Diameter:** 

0.032 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### Capacitance Value Per Section:

0.082 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

600.0 dc single section

## **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

Case Material:

Plastic

## **Terminal Surface Treatment:**

Solder

## **Dielectric Material:**

Plastic polypropylene

## Test Data Document:

81349-mil-c-55514 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

## **Specification Data:**

81349-mil-c-55514/10 government specification

#### Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No

# NSN 5910-01-434-7250

Plastic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

