

View Online at https://aerobasegroup.com/nsn/5910-01-434-7564

Body Style: Dual inline **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.001 **Body Length:** 0.092 inches **Body Width:** 0.260 inches **Body Height:** 0.128 inches Schematic Diagram Designator: No common or grounded electrode (s) Insulation Resistance At Maximum Operating Temp: 10000.0 megohms **Capacitance Value Per Section:** 680.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -30.0/+30.0 single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Plastic **Insulation Resistance At Reference Temp:** 100000.0 megohms **Terminal Surface Treatment:** Solder **Test Data Document:** 81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 printed circuit **Specification Data:** 81349-mil-c-39014/22 government specification

Shelf Life:

N/a



Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0