## NSN 5910-01-435-9588

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-435-9588 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.100 **Terminal Length:** 1.750 inches **Body Diameter:** Between 0.196 inches and 0.290 inches **Body Length:** Between 0.688 inches and 0.812 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 0.001 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material: Plastic Dissipation Factor At Reference Tempurature In Percent: Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polypropylene **Test Data Document:** 81349-mil-c-55514 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead **Specification Data:** 81349-mil-c-55514/10 government specification

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5910-01-435-9588

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0