## NSN 5910-01-437-2300

A010b0

Mil-std (military Standard):

Mil-c-39014 spec.

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-437-2300 **Body Style: Dual inline Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 0.010 **Body Length:** 0.092 inches **Body Width:** 0.260 inches **Body Height:** 0.283 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 680000.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Test Data Document:** 81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 printed circuit **Specification Data:** 81349-mil-c-39014/22 government specification Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: