

View Online at <https://aerobasegroup.com/nsn/5910-01-438-0734>

**Body Style:**

W/o mtg facilities, terminal (s) on one end

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

1.000

**Terminal Length:**

0.281 inches

**Body Diameter:**

1.375 inches

**Body Length:**

2.125 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

0.500 inches

**Terminal Diameter:**

0.312 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

2200.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 105.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Case Insulation Material:**

Plastic

**Test Data Document:**

81349-mil-c-39018 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 threaded hole

**Specification Data:**

81349-mil-c-39018/10 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0