## NSN 5910-01-440-9544

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-440-9544

**Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.0000 **Terminal Length:** 0.281 inches **Body Diameter:** 1.391 inches **Body Length:** 4.641 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.500 inches **Terminal Diameter:** 0.190 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 8700.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section **Tolerance Range Per Section:** -10.00/+50.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Case Insulation Material:** Plastic **Test Data Document:** 81349-mil-c-39018 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 

2 threaded hole

**Specification Data:** 

81349-mil-c-39018/6 government specification

Shelf Life:

N/a

## NSN 5910-01-440-9544

Electrolytic Fixed Capacitor - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A010b0