## NSN 5910-01-442-2595

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-442-2595
Body Style:
Chip type
Reliability Indicator:
Not established
Body Length:
0.063 inches
Body Width:
0.032 inches
Body Height:
0.035 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
Signal generator
Capacitance Value Per Section:
8.200 picofarads single section
Nonderated Operating Temp:
Nonderated Operating Temp.
Between -55.0 degrees celsius and 125.0 degrees celsius
Between -55.0 degrees celsius and 125.0 degrees celsius
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:  -0.25/+0.25 picofarads single section
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:  -0.25/+0.25 picofarads single section  Special Features:
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:  -0.25/+0.25 picofarads single section  Special Features:  No protective finish
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Special Features: No protective finish  Terminal Type And Quantity:
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Special Features: No protective finish  Terminal Type And Quantity: 2 bonding pad
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Special Features: No protective finish  Terminal Type And Quantity: 2 bonding pad  Shelf Life:
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Special Features: No protective finish  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Special Features: No protective finish  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Special Features: No protective finish  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a  Unit Of Measure:
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Special Features: No protective finish  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a  Unit Of Measure:  Demilitarization: