

View Online at https://aerobasegroup.com/nsn/5910-01-443-1440

Ceramic Dielectric Fixed Capacitor - Page 1 of 1

# Body Style:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.001

**Terminal Length:** 

1.250 inches

Body Length:

Between 0.180 inches and 0.200 inches

Body Width:

Between 0.180 inches and 0.200 inches

### **Body Height:**

Between 0.080 inches and 0.100 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.185 inches and 0.215 inches

#### **Terminal Diameter:**

Between 0.023 inches and 0.029 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### Capacitance Value Per Section:

33.000 picofarads single section

## Nonderated Operating Temp:

Between 55.0 degrees celsius and 125.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

## Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

#### Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0