Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-443-9596

## **Body Style:**

W/o mtg facilities, axial terminals

# **Reliability Indicator:**

Not established

### Body Diameter:

0.312 inches

#### **Body Length:**

0.641 inches

### Schematic Diagram Designator:

Electrod (s) grounded to case

### **Electrical Polarization:**

Polarized

#### Capacitance Value Per Section:

560.000 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

# **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

# Capacitive Electrode Material:

Tantalum

# Test Data Document:

14933-mil-std-202 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

#### Unit Of Measure:

```
---
```

Demilitarization:

No

Fiig:

A010b0