

View Online at <https://aerobasegroup.com/nsn/5910-01-446-8800>

**Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.100

**Terminal Length:**

1.500 inches

**Body Diameter:**

0.135 inches

**Body Length:**

0.286 inches

**Terminal Diameter:**

0.020 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case, w/gnd terminal

**Electrical Polarization:**

Polarized

**End Application:**

Radar warning system, litton systems inc, model an/anl-68 (v) -3

**Features Provided:**

Hermetically sealed case

**Capacitance Value Per Section:**

1.800 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

20.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Tantalum

**Case Insulation Material:**

Plastic

**Test Data Document:**

81349-mil-c-39003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Specification Data:**

81349-mil-c-39003/1 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0