

View Online at <https://aerobasegroup.com/nsn/5910-01-446-9773>

Body Style:

W/thd bushing mtg, terminals on opposite ends

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.1000

Terminal Length:

1.625 inches

Body Diameter:

0.670 inches

Body Length:

1.781 inches

Terminal Diameter:

0.032 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Internal Electrical Connection Type:

Extended foil

Mounting Facility Screw Thread Series Designator:

Unef

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

0.220 microfarads single section

Nonderated Operating Temp:

Between -65.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.438 inches

Nonderated Continuous Voltage Rating And Type Per Section:

600.0 dc single section

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-50.00/+50.00 single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Metal

Dissipation Factor At Reference Temperature In Percent:

0.6000

Terminal Surface Treatment:

Solder

Test Data Document:

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-19978/15 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0