NSN 5910-01-446-9796

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-446-9796

Body Style: W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 0.001 **Terminal Length:** 1.250 inches **Body Length:** 0.190 inches **Body Width:** 0.190 inches **Body Height:** 0.090 inches Center To Center Distance Between Terminals Parallel To Length: 0.200 inches **Terminal Diameter:** Between 0.020 inches and 0.027 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 2700.000 picofarads single section **Nonderated Operating Temp:** Between -55.00 degrees celsius and 125.00 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -30.0/+30.0 single section **Tolerance Range Per Section:** -1.00/+1.00 percent single section **Case Material:** Plastic **Terminal Surface Treatment:** Solder **Test Data Document:** 81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:**

N/a

Shelf Life:

2 uninsulated wire lead Specification Data:

81349-mil-c-20/35 government specification

NSN 5910-01-446-9796

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0