Plastic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-448-1893

# **Body Style:**

W/mtg bracket, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.010

### Body Diameter:

0.670 inches

**Body Length:** 

1.625 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### **Capacitance Value Per Section:**

0.100 microfarads single section

### Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

# **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

## **Case Material:**

Metal

# Test Data Document:

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

2 uninsulated wire lead

# **Specification Data:**

81349-mil-c-19978/17 government specification

Shelf Life:

N/a

## Unit Of Measure:

---

```
Demilitarization:
```

No

Fiig:

A010b0