Plastic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-448-4957

Body Style:

W/mtg bracket, axial terminals

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.010

Body Diameter:

0.562 inches

Body Length:

1.375 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

0.470 microfarads single section

Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Test Data Document:

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-19978/17 government specification

Shelf Life:

N/a

Unit Of Measure:

```
Demilitarization:
```

No

Fiig:

A010b0