Plastic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-448-9905

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.010

**Terminal Length:** 

2.625 inches

**Body Diameter:** 

0.400 inches

**Body Length:** 

0.833 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

**Capacitance Value Per Section:** 

0.018 microfarads single section

## Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Case Material:** 

Metal

## **Test Data Document:**

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

**Specification Data:** 

81349-mil-c-19978/18 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0