NSN 5910-01-449-1682

Plastic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-449-1682

| Body Style: |
|--|
| N/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 0.010 |
| Terminal Length: |
| 2.625 inches |
| Body Diameter: |
| 0.562 inches |
| Body Length: |
| 1.375 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 0.047 microfarads single section |
| Nonderated Operating Temp: |
| Between -65.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 1000.0 dc single section |
| Tolerance Range Per Section: |
| 2.00/+2.00 percent single section |
| Case Material: |
| Metal |
| Test Data Document: |
| 31349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Specification Data: |
| 31349-mil-c-19978/9 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| A010b0 |