NSN 5910-01-449-3132

Plastic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-449-3132 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 0.010 **Terminal Length:** 2.625 inches **Body Diameter:** 0.400 inches **Body Length:** 0.875 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 0.068 microfarads single section **Nonderated Operating Temp:** Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: Metal **Test Data Document:** 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead **Specification Data:** 81349-mil-c-19978/17 government specification Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

Fiig:

A010b0