Plastic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-450-0512

# **Body Style:**

W/mtg bracket, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.010

#### **Body Diameter:**

0.577 inches

**Body Length:** 

1.562 inches

## Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

**Capacitance Value Per Section:** 

0.470 microfarads single section

## Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

# **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

## **Case Material:**

Metal

# Test Data Document:

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-c-19978/17 government specification

Shelf Life:

N/a

# Unit Of Measure:

---

```
Demilitarization:
```

No

Fiig:

A010b0