## NSN 5910-01-451-1326

Plastic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-451-1326

| Body Style:  W/o mtg facilities, axial terminals  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.010  Terminal Length: 2.625 inches  Body Diameter: 0.562 inches  Body Length: 1.125 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section: 0.047 microfarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius |
|---|
| Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 2.625 inches Body Diameter: 0.562 inches Body Length: 1.125 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 0.047 microfarads single section Nonderated Operating Temp:  |
| Established  Reliability Failure Rate Level In Percent:  0.010  Terminal Length: 2.625 inches  Body Diameter: 0.562 inches  Body Length: 1.125 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Capacitance Value Per Section: 0.047 microfarads single section  Nonderated Operating Temp:   |
| Reliability Failure Rate Level In Percent:  0.010  Terminal Length: 2.625 inches  Body Diameter: 0.562 inches  Body Length: 1.125 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section: 0.047 microfarads single section  Nonderated Operating Temp:   |
| Terminal Length: 2.625 inches Body Diameter: 0.562 inches Body Length: 1.125 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 0.047 microfarads single section Nonderated Operating Temp:  |
| Terminal Length: 2.625 inches  Body Diameter: 0.562 inches  Body Length: 1.125 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Capacitance Value Per Section: 0.047 microfarads single section  Nonderated Operating Temp:   |
| 2.625 inches  Body Diameter: 0.562 inches  Body Length: 1.125 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Capacitance Value Per Section: 0.047 microfarads single section  Nonderated Operating Temp:  |
| Body Diameter:  0.562 inches  Body Length:  1.125 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  0.047 microfarads single section  Nonderated Operating Temp:  |
| 0.562 inches  Body Length: 1.125 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Capacitance Value Per Section: 0.047 microfarads single section  Nonderated Operating Temp:   |
| Body Length:  1.125 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  0.047 microfarads single section  Nonderated Operating Temp:  |
| 1.125 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  0.047 microfarads single section  Nonderated Operating Temp:  |
| Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  0.047 microfarads single section  Nonderated Operating Temp:  |
| No common or grounded electrode (s)  Capacitance Value Per Section:  0.047 microfarads single section  Nonderated Operating Temp:   |
| Capacitance Value Per Section:  0.047 microfarads single section  Nonderated Operating Temp:  |
| 0.047 microfarads single section  Nonderated Operating Temp:  |
| Nonderated Operating Temp:  |
|   |
| Between -55.0 degrees celsius and 125.0 degrees celsius   |
|   |
| Nonderated Continuous Voltage Rating And Type Per Section:  |
| 400.0 dc single section   |
| Tolerance Range Per Section:  |
| -5.00/+5.00 percent single section  |
| Case Material:  |
| Metal   |
| Test Data Document:   |
| 81340-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification  |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain   |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).   |
| Terminal Type And Quantity:   |
| 2 uninsulated wire lead   |
| Specification Data:   |
| 81349-mil-c-19978/8 government specification  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| -   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A010b0  |