Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-453-6550

Chip type Reliability Indicator: Not established Body Length: 0.287 inches Body Width: 0.170 inches Body Height: 0.170 inches Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Capacitance Value Per Section: 220.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius De Leakage At Maximum Operating Temp: 220.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section 10.0 dc single section Capacitive Electrode Material: 10.00/+10.00 percent single section Capacitive Electrode Material: 10.00/+10.00 percent single section Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Tempurature In Percent: 2.000 microamperes Terminal Type And Quantity: 2.000 microamperes Nat Unit Of Measure: <tr< th=""><th></th></tr<>	
Relability Indicator: Not established Body Length: 0.287 inches Body Width: 0.170 inches Body Height: 0.170 inches Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Capacitance Value Per Section: 2000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dectroal Polarization: 2000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dectroal Polarizet Out cost single section 10.00 d single section 10.00 vincoamperes Polacytive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 De Leakage At Reference Temp: 2.000 microamperes Terminal Type And Quantity: 2.000 microamperes Destif Life: N/a Liff Measure: Via	Body Style:
Not established Body Length: 0.287 inches Body Width: 0.170 inches Body Height: 0.170 inches Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Capacitance Value Per Section: 2000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Delakage At Maximum Operating Temp: 200 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.00 / 10.00 percent single section Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 De Leakage At Reference Tempurature In Percent: 2.000 microamperes Terminal Type And Quantity: 2.000 microamperes Desing pad Sheff Life: N/a Unit Of Measure: Panelind Type And Quantity: Na Sheff Life: N/a Dirit Of Measure:	
Body Length: 0.287 inches Body Width: 0.170 inches Body Height: 0.170 inches Body Height: 0.170 inches Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Capacitance Value Per Section: 220.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 220.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: 10.0 dc single section Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Tempurature In Percent: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: - Demilitarization: No	-
Notes Body Width: 0.170 inches Body Height: 0.170 inches Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Capacitance Value Per Section: 220.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius De Leakage At Maximum Operating Temp: 220.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section 12.0 domicroamperes 12.0 domicroamperes 12.0 domicroamperes 12.0 domicroamperes 12.0 domicroamperes 12.0 domicroamperes 12.1 domicroamperes	
Body Width: 0.170 inches Body Height: 0.170 inches Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Capacitance Value Per Section: 220.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 220.00 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.00/ +10.00 percent single section Capacitive Electrode Material: 10.00/+10.00 percent single section Capacitive Electrode Material: 20.00 microamperes Bould Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: - Permilitarization: No	
0.170 inchesBody Height:0.170 inchesSchematic Diagram Designator:No common or grounded electrode (s)Electrical Polarization:NonpolarizedCapacitance Value Per Section:220.000 microfarads single sectionMonderated Operating Temp:Between -55.0 degrees celsius and 85.0 degrees celsiusDe Leakage At Maximum Operating Temp:220.00 microamperesNonderated Continuous Voltage Rating And Type Per Section:10.0 dc single sectionTolerance Range Per Section:-10.00/+10.00 percent single sectionCapacitive Electrode Material:TantalumDissipation Factor At Reference Tempurature In Percent:8.000Dc Leakage At Reference Tempu22.000 microamperes2.000 microamperesYouNonderated Continuous Voltage Rating And Type Per Section:10.00/+10.00 percent single sectionCapacitive Electrode Material:2.000 microamperes2.000 microamperes2.000 microamperes2.000 microamperesPortinial Type And Quantity:2.000 microamperesNaUnit of Measure:NaDisting Factor Reference Temp:NaDisting FactorMain Continue Reference Temp:2.000 microamperesFerminal Type And Quantity:2.100 microamperesNaDisting FactorNaDisting FactorNaDisting FactorNaDisting Factor </td <td></td>	
Body Height: 0.170 inches Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Capacitance Value Per Section: 220.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 220.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: 10.0 dc single section Tolerance Range Per Section: 10.00/+10.00 percent single section Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	-
0.170 inches Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Capacitance Value Per Section: 220.000 microfarads single section 220.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 220.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: 	0.170 inches
Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Capacitance Value Per Section: 220.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 220.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Height:
No common or grounded electrode (s) Electrical Polarization: Nonpolarized Capacitance Value Per Section: 220.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 220.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.170 inches
Electrical Polarization: Nonpolarized Capacitance Value Per Section: 220.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 220.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Schematic Diagram Designator:
Nonpolarized Capacitance Value Per Section: 220.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 220.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	No common or grounded electrode (s)
Capacitance Value Per Section:220.000 microfarads single sectionNonderated Operating Temp:Between -55.0 degrees celsius and 85.0 degrees celsiusDe Leakage At Maximum Operating Temp:220.0 microamperesNonderated Continuous Voltage Rating And Type Per Section:10.0 dc single sectionTolerance Range Per Section:-10.00/+10.00 percent single sectionCapacitive Electrode Material:TantalumDissipation Factor At Reference Tempurature In Percent:8.000Dc Leakage At Reference Temp:22.000 microamperesTerminal Type And Quantity:2 bonding padShelf Life:N/aUnit Of Measure:-Demilitarization:No	Electrical Polarization:
220.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 220.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Capacitive Electrode Material: -10.00/+10.00 percent single section -10.00/+10.00 percent singl	Nonpolarized
Nonderated Operating Temp:Between -55.0 degrees celsius and 85.0 degrees celsiusDc Leakage At Maximum Operating Temp:220.0 microamperesNonderated Continuous Voltage Rating And Type Per Section:10.0 dc single sectionTolerance Range Per Section:-10.00/+10.00 percent single sectionCapacitive Electrode Material:TantalumDissipation Factor At Reference Tempurature In Percent:8.000Dc Leakage At Reference Temp:22.000 microamperesTerminal Type And Quantity:2 bonding padShelf Life:N/aUnit Of Measure:-No	Capacitance Value Per Section:
Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 220.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	220.000 microfarads single section
Dc Leakage At Maximum Operating Temp: 220.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Nonderated Operating Temp:
220.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Dc Leakage At Maximum Operating Temp:
10.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	220.0 microamperes
Tolerance Range Per Section: -10.00/+10.00 percent single section Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Nonderated Continuous Voltage Rating And Type Per Section:
-10.00/+10.00 percent single section Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	10.0 dc single section
Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Tolerance Range Per Section:
Tantalum Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	-10.00/+10.00 percent single section
Dissipation Factor At Reference Tempurature In Percent: 8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	Capacitive Electrode Material:
8.000 Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	Tantalum
Dc Leakage At Reference Temp: 22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Dissipation Factor At Reference Tempurature In Percent:
22.000 microamperes Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	8.000
Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Dc Leakage At Reference Temp:
2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	22.000 microamperes
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No	2 bonding pad
Unit Of Measure: Demilitarization: No	Shelf Life:
 Demilitarization: No	N/a
Νο	Unit Of Measure:
Νο	
	Demilitarization:
Fiiq:	No
0	Fiig:
A010b0	-