Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-455-7473

Reliability Indicator: Not established End Application: Seahawk helicopter Capacitance Value Per Section: 47.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section -10.00/+100.00 percent single section Capacitive Electrode Material: Aluminum Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Pemilitarization: Yes - demil/mli		
End Application: Seahawk helicopter Capacitance Value Per Section: 47.000 microfarads single section Aronderated Operating Temp: Between -55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section Tolerance Range Per Section: -10.00/+100.00 percent single section Capacitive Electrode Material: Aluminum Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Reliability Indicator:	
Seahawk helicopter Capacitance Value Per Section: 47.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section Tolerance Range Per Section: -10.00/+100.00 percent single section Capacitive Electrode Material: Aluminum Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Not established	
Capacitance Value Per Section:47.000 microfarads single sectionNonderated Operating Temp:Between -55.0 degrees celsius and 105.0 degrees celsiusNonderated Continuous Voltage Rating And Type Per Section:25.0 dc single sectionTolerance Range Per Section:-10.00/+100.00 percent single sectionCapacitive Electrode Material:AluminumTerminal Type And Quantity:2 uninsulated wire leadShelf Life:N/aUnit Of Measure:Demilitarization:Yes - demil/mli	End Application:	
47.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section Tolerance Range Per Section: -10.00/+100.00 percent single section Capacitive Electrode Material: Aluminum Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Seahawk helicopter	
Nonderated Operating Temp: Between -55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section Tolerance Range Per Section: -10.00/+100.00 percent single section Capacitive Electrode Material: Aluminum Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Capacitance Value Per Section:	
Between -55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section Tolerance Range Per Section: -10.00/+100.00 percent single section Capacitive Electrode Material: Aluminum Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	47.000 microfarads single section	
Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section Tolerance Range Per Section: -10.00/+100.00 percent single section Capacitive Electrode Material: Aluminum Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Nonderated Operating Temp:	
25.0 dc single section Tolerance Range Per Section: -10.00/+100.00 percent single section Capacitive Electrode Material: Aluminum Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Between -55.0 degrees celsius and 105.0 degrees celsius	
Tolerance Range Per Section: -10.00/+100.00 percent single section Capacitive Electrode Material: Aluminum Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Nonderated Continuous Voltage Rating And Type Per Section:	
-10.00/+100.00 percent single section Capacitive Electrode Material: Aluminum Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	25.0 dc single section	
Capacitive Electrode Material: Aluminum Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Tolerance Range Per Section:	
Aluminum Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	-10.00/+100.00 percent single section	
Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Capacitive Electrode Material:	
2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Aluminum	
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Terminal Type And Quantity:	
N/a Unit Of Measure: Demilitarization: Yes - demil/mli	2 uninsulated wire lead	
Unit Of Measure: Demilitarization: Yes - demil/mli	Shelf Life:	
 Demilitarization: Yes - demil/mli	N/a	
Demilitarization: Yes - demil/mli	Unit Of Measure:	
Yes - demil/mli		
	Demilitarization:	
Fiig:	Yes - demil/mli	
	Fiig:	

A010b0