NSN 5910-01-456-4225



Electrolytic Fixed Capacitor - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5910-01-456-4225 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.100 **Terminal Length:** Between 1.250 inches and 1.750 inches **Body Diameter:** Between 0.335 inches and 0.367 inches **Body Length:** Between 0.750 inches and 0.817 inches **Terminal Diameter:** Between 0.023 inches and 0.027 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 470.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.00 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Tantalum Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiid

Fiig:

A010b0