NSN 5910-01-458-0794

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-458-0794 **Body Style:** W/o mtg facilities, terminals on opposite surfaces **Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 0.010 **Terminal Length:** Between 0.120 inches and 0.160 inches **Body Length:** Between 0.240 inches and 0.280 inches **Body Width:** Between 0.086 inches and 0.098 inches **Body Height:** 0.195 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 220.000 nanofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Test Data Document:**

81349-mil-prf-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-prf-39014/22 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0

Mil-std (military Standard):

Mil-prf-39014 spec.