NSN 5910-01-463-9688

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-463-9688

Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Body Diameter:
0.696 inches
Body Length:
1.250 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
An/apq170 rad e/i fscm 56289
Capacitance Value Per Section:
0.470 microfarads single section
Nonderated Operating Temp:
Between 55.0 degrees celsius and 105.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
700.0 ac-peak single section and 630.0 dc single section
700.0 ac-peak single section and 630.0 dc single section
700.0 ac-peak single section and 630.0 dc single section Tolerance Range Per Section:
700.0 ac-peak single section and 630.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section
700.0 ac-peak single section and 630.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity:
700.0 ac-peak single section and 630.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 uninsulated wire lead
700.0 ac-peak single section and 630.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
700.0 ac-peak single section and 630.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
700.0 ac-peak single section and 630.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
700.0 ac-peak single section and 630.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
700.0 ac-peak single section and 630.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization:
700.0 ac-peak single section and 630.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No
700.0 ac-peak single section and 630.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
700.0 ac-peak single section and 630.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: