## NSN 5910-01-465-2183

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-465-2183 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.001 **Body Length:** 0.190 inches **Body Width:** 0.190 inches **Body Height:** 0.090 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **End Application:** lu jtids jsta **Capacitance Value Per Section:** 100.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Special Features:** This drawing meets and exceeds mil-prf-39014 with added solderability requirements **Test Data Document:** 08748-ca200 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure:** 

Demilitarization: No

Fiig: A010b0

Mil-std (military Standard):

Mil-prf-39014 spec.