

View Online at <https://aerobasegroup.com/nsn/5910-01-465-2262>

**Body Style:**

Chip type

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.010

**Body Length:**

0.180 inches

**Body Width:**

0.125 inches

**Body Height:**

0.080 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**End Application:**

Iu jtids jsta

**Capacitance Value Per Section:**

100000.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Special Features:**

This drawing meets and exceeds mil-prf-55681 with additional solderability requirements

**Test Data Document:**

08748-ca200 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

2 bonding pad

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0

**Mil-std (military Standard):**

Mil-prf-55681 spec.